



# SAFETY DATA SHEET

## BOSTIK ACRYL 65 M

### 1. Identification of the substance/preparation and company/undertaking

#### Identification of the substance or preparation

**Product name** : BOSTIK ACRYL 65 M  
**Code** : 508290  
**Use of the substance/preparation** : Putty. Acrylic.  
**Manufacturer** : BOSTIK SA  
 Immeuble IRIS  
 92062 PARIS LA DEFENSE Cedex  
 FRANCE  
**Telephone no.** : + 33 (0) 1 47 96 94 65  
**Fax no.** : + 33 (0) 1 47 96 96 90  
**Emergency telephone number** : + 33 (0) 1 45 42 59 59

### 2. Composition/information on ingredients

**Substance/preparation** : Preparation  
**Nature of material** : Putty.

Ingredient name	CAS number	%	EC number	Classification
1,2-benzenedicarboxylic acid, bis(2-methylpropyl) ester	84-69-5	1 - 5	201-553-2	N; R50
talc , not containing asbestiform fibres	14807-96-6	1 - 5	238-877-9	Not classified.
titanium dioxide	13463-67-7	1 - 5	236-675-5	Not classified.
lubricating oils	74869-22-0	< 1	278-012-2	Carc. Cat. 2; R45
<b>See section 16 for the full text of the R-phrases declared above</b>				

Occupational exposure limits, if available, are listed in section 8.

### 3. Hazards identification

The product is classified as dangerous according to Directive 1999/45/EC and its amendments.

**Classification** : Carc. Cat. 2; R45  
**Human health hazards** : May cause cancer.

See section 11 for more detailed information on health effects and symptoms.

### 4. First-aid measures

#### First-aid measures

- Inhalation** : Get medical attention immediately. Move exposed person to fresh air. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Ingestion** : Get medical attention immediately. Wash out mouth with water. Remove dentures if any. Move exposed person to fresh air. Keep person warm and at rest. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen

- tight clothing such as a collar, tie, belt or waistband.
- Skin contact** : Get medical attention immediately. Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention if irritation occurs.

See section 11 for more detailed information on health effects and symptoms.

## 5. Fire-fighting measures

### Extinguishing media

- Suitable** : Use an extinguishing agent suitable for the surrounding fire.
- Not suitable** : None known.

**Special exposure hazards** : In a fire or if heated, a pressure increase will occur and the container may burst. Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

**Hazardous thermal decomposition products** : Decomposition products may include the following materials:  
carbon dioxide  
carbon monoxide  
metal oxide/oxides

**Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

## 6. Accidental release measures

**Personal precautions** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see section 8).

**Environmental precautions** : Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

**Methods for cleaning up** : Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Note: see section 1 for emergency contact information and section 13 for waste disposal.

## 7. Handling and storage

**Handling** : Put on appropriate personal protective equipment (see section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Avoid exposure - obtain special instructions before use. Do not get in eyes or on skin or clothing. Do not breathe vapour or mist. Do not ingest. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

**Storage** : Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

### Packaging materials

**Recommended** : Use original container.

## 8. Exposure controls/personal protection

**Ingredient name****Occupational exposure limits**

talc , not containing asbestiform fibres

**ACGIH TLV (United States, 1/2007).**TWA: 2 mg/m<sup>3</sup> 8 hour(s).

titanium dioxide

**ACGIH TLV (United States, 1/2007).**TWA: 10 mg/m<sup>3</sup> 8 hour(s).

### Exposure controls

**Occupational exposure controls**

: If user operations generate dust, fumes, gas, vapour or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

**Respiratory protection**

: Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

**Hand protection**

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

**Eye protection**

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts.

**Skin protection**

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period.

Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

**Environmental exposure controls**

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

## 9. Physical and chemical properties

### General information

**Appearance****Physical state** : Liquid. [Paste.]**Colour** : White.**Odour** : Slight

### Important health, safety and environmental information

**pH** : 7 to 9**Boiling point** : 100°C (212°F)**Melting point** : 0°C (32°F)**Relative density** : 1,57 g/cm<sup>3</sup> [23°C (73,4°F)]**Solubility** : Insoluble in the following materials: cold water and hot water.**Dispersibility properties** : Dispersible in the following materials: cold water and hot water.

## 10. Stability and reactivity

**Stability** : The product is stable.**Hazardous decomposition products** : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## 11. Toxicological information

### Potential acute health effects

- Inhalation** : No known significant effects or critical hazards.  
**Ingestion** : No known significant effects or critical hazards.  
**Skin contact** : No known significant effects or critical hazards.  
**Eye contact** : No known significant effects or critical hazards.

### Potential chronic health effects

- | <u>Ingredient name</u> | <u>Carcinogenic effects</u> | <u>Mutagenic effects</u> | <u>Developmental toxicity</u> | <u>Impairs fertility</u> |
|------------------------|-----------------------------|--------------------------|-------------------------------|--------------------------|
| lubricating oils       | Carc. Cat. 2; R45           | -                        | -                             | -                        |
- Carcinogenicity** : May cause cancer. Risk of cancer depends on duration and level of exposure.  
**Mutagenicity** : No known significant effects or critical hazards.  
**Reproductive toxicity** : No known significant effects or critical hazards.

### Over-exposure signs/symptoms

- Inhalation** : No known significant effects or critical hazards.  
**Ingestion** : No known significant effects or critical hazards.  
**Skin** : No known significant effects or critical hazards.  
**Target organs** : Contains material which may cause damage to the following organs: lungs, cardiovascular system, upper respiratory tract, skin, eye, lens or cornea.

## 12. Ecological information

### Ecotoxicity data

<u>Ingredient name</u>	<u>Species</u>	<u>Period</u>	<u>Result</u>
1,2-benzenedicarboxylic acid, bis(2-methylpropyl) ester	Pimephales promelas (LC50) Daphnia (EC50) Algae (EC50)	96 hour(s) 24 hour(s) 72 hour(s)	0.9 mg/l 7.4 mg/l 2.2 mg/l
titanium dioxide	Daphnia magna (EC50)	48 hour(s)	>1000 mg/l

- Other adverse effects** : No known significant effects or critical hazards.

## 13. Disposal considerations

- Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.
- Hazardous waste** : The classification of the product may meet the criteria for a hazardous waste.

## 14. Transport information

### International transport regulations

Regulatory information	UN number	Proper shipping name	Class	Packing group	Label	Additional information
<b>ADR/RID Class</b>	Not regulated.	-	-	-		-
<b>ADNR Class</b>	Not regulated.	-	-	-		-
<b>IMDG Class</b>	Not regulated.	-	-	-		-
<b>IATA Class</b>	Not regulated.	-	-	-		-

## 15. Regulatory information

### EU regulations

Hazard symbol or symbols :



Toxic

**Risk phrases** : R45- May cause cancer.

**Safety phrases** : S53- Avoid exposure - obtain special instructions before use.  
S2- Keep out of the reach of children.

**Contains** : lubricating oils

**Product use** : Consumer applications.

### Other EU regulations

**Child protection** : Yes, applicable.

**Tactile warning of danger** : Yes, applicable.

**Restrictions on the Marketing and Use Directive** : Restricted to professional users.

## 16. Other information

**Full text of R-phrases referred to in sections 2 and 3 - Europe** : R45- May cause cancer.  
R50- Very toxic to aquatic organisms.

**Full text of classifications referred to in sections 2 and 3 - Europe** : Carc. Cat. 2 - Carcinogen Category 2  
N - Dangerous for the environment

### History

**Date of printing** : 03/12/2007.

**Validation date** : 03/12/2007.

**Date of previous issue** : No previous validation.

**Version** : 1

### Notice to reader

*To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.*

*Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.*